

20W-50 HTC

DATASHEET

TECHNICAL PHYSICAL DATA	
SAE GRADE	20W50
DENSITY AT 15 °C. (ASTM D1298)	0,890
VISCOSITY 40 °C. cST. (ASTM D445)	165
VISCOSITY 100 °C. cST. (ASTM D445)	18
VISCOSITY INDEX, (ASTM D2270)	125
FLASH POINT °C. (ASTM D92)	230
FREEZING POINT °C. (ASTM D97)	-18
TBN. (ASTM D-2896)	10

RECOMMENDATIONS	
MB 229.0 The 228.3	VOLVO VDS 2
VW 501.01 / VW 505.00	PERSON TYPE 1
ALLISON C4	PSA-PEUGEOT-CITROËN

DESCRIPTION

ADVANCE 20W-50 HTB IS A LATEST GENERATION SUPERMULTIGRADE OIL, SPECIAL FOR 4-STROKE GASOLINE AND LIGHT DIESEL ENGINES, INCLUDING THOSE OF THE GTI-TDI-HDI TYPE, WHERE THE MANUFACTURER REQUESTS THIS SAE GRADE. THIS LUBRICANT IS COMPOSED OF THE BEST HIGHLY REFINED BASES AND THE MOST MODERN SYNTHETIC ADDITIVES, WHICH GUARANTEE PERFECT LUBRICATION UNDER ALL CONDITIONS OF USE.

- **MAIN ADVANTAGES**
- **EXCELLENT LUBRICANT AND ANTI-WEAR PROPERTIES.**
- **GREAT RESISTANCE TO OXIDATION AND AGING.**
- **HIGH DETERGENT AND DISPERSANT POWER.**
- **GOOD PROTECTION AGAINST CORROSION.**
- **DECREASES OIL CONSUMPTION. USABLE IN WINTER AND SUMMER.**
- **SUITABLE FOR LIGHT GASOLINE AND DIESEL VEHICLE.**
- **INCREASES THE OIL CHANGE PERIOD AND CONSEQUENTLY REDUCES THE MAINTENANCE COST.**
- **LUBRICANT TO BE USED WHERE THE MANUFACTURER REQUESTS THESE QUALITY LEVELS.**

QUALITY LEVELS	
ACEA	A3/B4
API	SM / CF-4
MIL	L46152 B L21104 E