

## MB 236.14

## DATASHEET

TECHNICAL PHYSICAL DATA	
COLOR	RED
DENSITY AT 15 °C, g/ml (ASTM D4052)	0,849
VISCOSITY 100 °C. cST. (ASTM D445)	6,4
VISCOSITY INDEX, (ASTM D2270)	185
FLASH POINT °C. (ASTM D92)	200
FREEZING POINT °C. (ASTM D97)	-51
COPPER CORROSION	NO
CORROSION TO STEEL	NO

### DESCRIPTION

**TORQUE A.T.F. 236.14 IS A 100% SYNTHETIC AUTOMATIC TRANSMISSION FLUID SPECIALLY DESIGNED FOR ALL MERCEDES CARS WITH REAR WHEEL DRIVE (RWD) AND ALL WHEEL DRIVE (AWD), AS WELL AS SUV AND LIGHT UTILITY VEHICLES EQUIPPED WITH AUTOMATIC GEARBOXES. SPECIALLY ADAPTED FOR ALL MERCEDES MODELS EQUIPPED WITH RWD 7 SPEED AUTOMATIC GEARBOXES (NAG2) AND ALL AMG MODELS WHERE THE MANUFACTURER REQUIRES SPECIFICATION MB 236.14. RECOMMENDED FOR MERCEDES RWD 4 AND 5 SPEED AUTOMATIC GEARBOXES. MANUFACTURED WITH 100% SYNTHETIC BASE STOCKS AND HIGH-TECH SYNTHETIC ADDITIVES THAT GUARANTEE THE HIGHEST AND TOUGHEST APPLICATION REQUIREMENTS. COMPARED TO CONVENTIONAL ATFS, IT HAS EXCEPTIONAL FLOW PROPERTIES AT LOW TEMPERATURES AND IMPROVED PROTECTION AGAINST VISCOSITY FAILURE AT HIGH TEMPERATURES. IT ALSO HAS SUPERIOR OXIDATION STABILITY AND THERMAL STABILITY, RESULTING IN INCREASED SERVICE LIFE.**

### MAIN ADVANTAGES

- EXCELLENT LUBRICANT AND ANTI-WEAR PROPERTIES.
- GREAT RESISTANCE TO OXIDATION AND AGING.
- MINIMAL FOAM FORMATION, AND ALMOST NO SLUDGE.
- VERY HIGH VISCOSITY INDEX.
- COMPATIBILITY WITH GASKETS AND SEALANTS.
- MAINTAINS FRICTION CONTROL TO ALLOW SMOOTH GEAR SHIFT ACTION.
- MAINTAINS FLUIDITY AT LOW TEMPERATURE AND STABILITY AT HIGH TEMPERATURE DURING LONG OPERATIONAL PERIODS.
- QUIET PERFORMANCE THAT GUARANTEES UNIFORM AND SILENT ACTION AT ALL SPEED REGIMES.
- THE USE OF THIS FLUID REQUIRES VERIFICATION OF THE MANUFACTURERS' SPECIFICATIONS, AND THAT IT BE USED FOLLOWING THE INSTRUCTIONS OF THE VEHICLE MANUFACTURER.
- THIS PRODUCT IS NOT SUITABLE FOR CONTINUOUS VARIABLE TRANSMISSION OR CVT, NOR IN DOUBLE CLUTCH GEARBOXES (DSG OR DCT).

### QUALITY LEVELS

MB 236.14 / MB 236.12
MB NAG-2 Transmissions
MB 722.9 Series 7 Speed Transmissions
MB 722.6 Series 5-Speed Transmissions
(W5A 580/NAG1)
Ssang Yong passenger cars and other vehicles with MB automatic transmission requesting MB 236.14
Valid for use where the manufacturer requests MB 236.1 - MB 236.6 - 236.7 - 236.9 - 236.10