

TORQUE

STEERING FLUID



PSF HONDA

DATASHEET

TECHNICAL PHYSICAL DATA	
COLOR	LIGHT AMBER
VISCOSITY 100 °C.	12,50 cST
VISCOSITY 40 °C.	45/55 cST
VISCOSITY -40 °C.	11900
VISCOSITY INDEX	>260
FLASH POINT °C.	>155
FREEZING POINT °C.	-50

DESCRIPTION

TORQUE P.S.F. HONDA IS A SPECIALLY FORMULATED FLUID WITH 100% SYNTHETIC PAO BASES AND LATEST GENERATION ADDITIVES FOR HYDRAULIC CIRCUITS, SPECIFICALLY DEVELOPED FOR USE IN HONDA AND ACURA VEHICLES. ITS USE IS INTENDED FOR VEHICLES EQUIPPED WITH HYDRAULIC CIRCUIT, POWER STEERING, BRAKES, CUSHIONING AND HYDROPNEUMATIC SUSPENSIONS, WHICH REQUEST THE SPECIFIED QUALITY LEVELS.

• MAIN ADVANTAGES

- EXCELLENT LUBRICANT AND ANTI-WEAR PROPERTIES.
- GREAT RESISTANCE TO OXIDATION AND AGING.
- MINIMAL FOAM FORMATION, AND ALMOST NO SLUDGE.
- VERY HIGH VISCOSITY INDEX.
- COMPATIBILITY WITH GASKETS AND SEALANTS.
- DO NOT MIX WITH CONVENTIONAL BRAKE FLUIDS.
- DO NOT MIX WITH MINERAL-BASED FLUIDS L.H.M.
- DO NOT USE FOR AUTOMATIC GEARBOXES, NOR MIX WITH A.T.F TYPE LUBRICANT.
- THE USE OF THIS FLUID REQUIRES VERIFICATION OF THE MANUFACTURERS' SPECIFICATIONS, AND THAT IT BE USED FOLLOWING THE INSTRUCTIONS OF THE VEHICLE MANUFACTURER.

QUALITY LEVELS

Acura P/N 08206-9002A
Honda P/N 08206-9002A
Honda PSF-2
Honda PSF Type S
Honda PSF Type V