

TORQUE

HYDRAULIC FLUID



LDS

DATASHEET

TECHNICAL PHYSICAL DATA	
COLOR	ORANGE
mitsubishi - PS FLUID Y SPIII	0,835
VISCOSITY 100 °C.	6,2 cST
VISCOSITY 40 °C.	18,9 cST
VISCOSITY -40 °C.	<2000
VISCOSITY INDEX	>280
FLASH POINT °C.	>160
BOILING POINT °C.	>235
FREEZING POINT °C.	-51

DESCRIPTION

TORQUE L.D.S. HIDRACTIV 3 AND 3+ IS A FLUID SPECIALLY FORMULATED WITH SYNTHETIC HYDROCARBONS FOR HYDRAULIC CIRCUITS SPECIFICALLY DEVELOPED FOR USE IN VEHICLES EQUIPPED WITH HIDRACTIV 3 AND 3+ HYDROPNEUMATIC POWER STEERING, USED BY CITRÖEN, PEUGEOT, ETC. ITS USE IS INTENDED EXCLUSIVELY FOR VEHICLES THAT REQUEST THE SPECIFIED QUALITY LEVELS.

• MAIN ADVANTAGES

- EXCELLENT LUBRICANT AND ANTI-WEAR PROPERTIES.
- GREAT RESISTANCE TO OXIDATION AND AGING.
- MINIMAL FOAM FORMATION, AND ALMOST NO SLUDGE.
- VERY HIGH VISCOSITY INDEX.
- COMPATIBILITY WITH GASKETS AND SEALANTS.
- DO NOT MIX WITH CONVENTIONAL BRAKE FLUIDS.
- DO NOT MIX WITH MINERAL-BASED FLUIDS L.H.M.
- DO NOT USE FOR AUTOMATIC GEARBOXES, NOR MIX WITH A.T.F TYPE LUBRICANT.
- THE USE OF THIS FLUID REQUIRES VERIFICATION OF THE MANUFACTURERS' SPECIFICATIONS, AND THAT IT BE USED FOLLOWING THE INSTRUCTIONS OF THE VEHICLE MANUFACTURER.
- THIS PRODUCT IS NOT SUITABLE FOR CONTINUOUSLY VARIABLE TRANSMISSION OR CVT, NOR IN DOUBLE CLUTCH GEARBOXES (DSG OR CVT).

QUALITY LEVELS

PSA S71 2710

MAN 3289

RENAULT PSF CLASSE 1