

# PERFORMANCE

## VTS



# 5W-30 GTC

## DATASHEET

TECHNICAL PHYSICAL DATA	
SAE GRADE	5W30
VISCOSITY 100 °C. cST.(ASTM D445)	12
VISCOSITY 40 °C. cST.(ASTM D445)	74
VISCOSITY INDEX, (ASTM D2270)	160
FLASH POINT °C. (ASTM D92)	225
FREEZING POINT °C. (ASTM D97)	-40
SULFATED ASH % by weight (ASTM D874)	0.80
TBN. (ASTM D-2896)	>6

RECOMMENDATIONS
MB 229.51 - 229.31
VW 504.00 / 507.00
BMW LL04
PORSCHE C30

### DESCRIPTION

VTS 5W-30 GTC C3 IS A HIGH QUALITY 100% SYNTHETIC LUBRICANT, BASED ON PAO AND GROUP III SYNTHETIC BASES WITH SPECIFIC LATEST GENERATION ADDITIVES, INDICATED FOR USE IN THE MOST MODERN GASOLINE AND DIESEL ENGINES OF THE VAG GROUP ( VW, AUDI, SEAT AND SKODA), BMW AND MERCEDES BENZ

### MAIN ADVANTAGES

- EXCELLENT LUBRICANT AND ANTI-WEAR PROPERTIES.
- GREAT RESISTANCE TO OXIDATION AND AGING.
- HIGH DETERGENT AND DISPERSANT POWER.
- GOOD PROTECTION AGAINST CORROSION.
- DECREASES OIL CONSUMPTION.
- USABLE IN WINTER AND SUMMER.
- INCREASES THE OIL CHANGE PERIOD AND CONSEQUENTLY REDUCES THE MAINTENANCE COST.
- LUBRICANT TO BE USED WHERE THE MANUFACTURER REQUESTS THESE QUALITY LEVELS.

QUALITY LEVELS	
ACEA	C3
API	SM / CF