

PERFORMANCE VTX



0W-20 LTD

DATASHEET

TECHNICAL PHYSICAL DATA	
SAE GRADE	0W20
VISCOSITY 100 oC. cST.(ASTM D445)	8,6
VISCOSITY INDEX, (ASTM D2270)	169
FLASH POINT °C. (ASTM D92)	>210
FREEZING POINT °C. (ASTM D97)	-40
SULFATED ASH % by weight (ASTM D874)	0.9
TBN. (ASTM D-2896)	>8

BUILDERS
FORD WSS-M2C947-A / WSS-M2C962-A1
RETRO APPLICABLE FORD 946 AND 945
GM DEXOS 1 (Gen.2) / 4718M - 6094M
CHRYSLER MS 6395

DESCRIPTION

PERFORMANCE VTX 0W20 LTD GF-6A/FORD 947 (FUEL ECONOMY) IS A 100% SYNTHETIC LUBRICANT, SPECIFICALLY DEVELOPED FOR LATEST FORD GASOLINE AND DIESEL ENGINES WITH TURBO, ATMOSPHERIC, OR DIRECT INJECTION WHERE THE MANUFACTURER RECOMMENDS THE FORD SPECIFICATION 947- A, FORD WSS-M2C962-A1 AND GM DEXOS 1 (Gen.2). IT IS SPECIALLY ADAPTED TO LATEST GENERATION GASOLINE ENGINES "DOWNSIZING", "STOP & START" SYSTEMS AND HYBRID ENGINES, WHICH REQUIRE A 100% SYNTHETIC LUBRICANT. SUITABLE FOR THE MOST SEVERE CONDITIONS OF USE. THE 0W-20 GRADE ALLOWS YOU TO REDUCE THE INTERNAL FRICTIONS OF THE ENGINE AND THUS EXTRACT THE POWER, MAKING SAVINGS ON FUEL CONSUMPTION. THIS LUBRICANT ALLOWS YOU TO MAKE FUEL SAVINGS WITHOUT CHANGE YOUR DRIVING HABITS, IT IS ALSO FRIENDLY FOR THE ENVIRONMENT BY MINIMIZING EMISSIONS OF POLLUTING GREENHOUSE GAS (CO₂).

INTERVALS: APPLY ACCORDING TO THE VEHICLE MANUFACTURER'S RECOMMENDATION AND ADAPTED TO YOUR OWN USE.

MAIN ADVANTAGES

- EXCELLENT LUBRICANT AND ANTI-WEAR PROPERTIES.
- GREAT RESISTANCE TO OXIDATION AND AGING.
- HIGH DETERGENT AND DISPERSANT POWER.
- GOOD PROTECTION AGAINST CORROSION.
- DECREASES OIL CONSUMPTION.
- USABLE IN WINTER AND SUMMER.
- REDUCES MAINTENANCE COST.
- LUBRICANT TO BE USED WHERE THE MANUFACTURER REQUESTS THESE QUALITY LEVELS.
- IMPROVE COLD STARTING IN ALL SEASONS.
- HIGH PROTECTION AGAINST LSPI (LOW SPEED PREIGNITION).

QUALITY LEVELS	
ILSAC	GF-6A
API	SN+(RC) SP