

# PERFORMANCE VTX



## 5W-30 LTN

### DATASHEET

TECHNICAL PHYSICAL DATA	
SAE GRADE	5W30
VISCOSITY 100 °C. cST. (ASTM D445)	10
VISCOSITY INDEX, (ASTM D2270)	170
FLASH POINT °C. (ASTM D92)	225
FREEZING POINT °C. (ASTM D97)	-40
TBN. (ASTM D-2896)	>10

BUILDERS
FORD WSS-M2C913-D, WSS-M2C913-C, WSS-M2C913-B, WSS-M2C913-A.
JAGUAR LAND ROVER - STJR.03.5003

### DESCRIPTION

PERFORMANCE VTX 5W30 LTN A5/B5, IS A 100% SYNTHETIC LUBRICANT, SPECIALLY DESIGNED FOR USE IN LIGHT GASOLINE AND DIESEL ENGINES, (WITH AND WITHOUT CATALYST) INCLUDING HIGH POWER AND MULTI-VALVE TURBO CHARGED UNITS. LUBRICANT TO BE USED IN ALL VEHICLES WHERE SPECIFICATIONS ARE REQUIRED, Ford WSS-M2C913-D, WSS-M2C913-C, WSS-M2C913-B AND WSS-M2C913-A. RECOMMENDED FOR A LONG CHANGE INTERVAL ACCORDING TO EACH MANUFACTURER'S RECOMMENDATIONS. IT HAS EXCELLENT COLD BEHAVIOR DUE TO ITS DESIGNED LOW VISCOSITY AND ITS SYNTHETIC NATURE, WHICH FACILITATES THE PUMPABILITY OF THE LUBRICANT, A REASON OF GREAT HELP IN COLD STARTING AND FILM FORMATION TO IMPORTANTLY REDUCE WEAR.

### MAIN ADVANTAGES

- EXCELLENT LUBRICANT AND ANTI-WEAR PROPERTIES.
- GREAT RESISTANCE TO OXIDATION AND AGING.
- HIGH DETERGENT AND DISPERSANT POWER.
- GOOD PROTECTION AGAINST CORROSION.
- DECREASES OIL CONSUMPTION.
- USABLE IN WINTER AND SUMMER.
- REDUCES MAINTENANCE COST.
- LUBRICANT TO BE USED WHERE THE MANUFACTURER REQUESTS THESE QUALITY LEVELS.
- IMPROVE COLD STARTING IN ALL SEASONS

QUALITY LEVELS	
ACEA	A5/B5 A1/B1
API	SM - CF
ILSAC	GF-5